

Product Info

"USBcan Light HS/HS"

(Manufacturer: Kvaser AB)



The Kvaser USBcan Light 2xHS is a compact, reliable and cost-effective means of connecting two high speed CAN busses to a PC or mobile computer. With a USB 2.0 compliant connector at one end and two 9-pin D-SUB connector at the other, the Kvaser USBcan Light 2xHS is a fraction larger than one-channel Leaf Light v2 but features the same sleek, ergonomically for and comes with galvanic isolation as standard.

The Kvaser USBcan Light 2xHS offers two high speed CAN channels and one USB 2.0 compliant interface. With the tree connectors at the end of fully galvanically isolated flexible wires, this device is designed to facilitate any application in which the CAN bus connectors aren't easily accessible, such as hard to reach electronic control units (EDU) on a vehicle. USBcan Light 2xHS is supplied with CANlib, the Software API that is common to all Kvaser hardware. Taking just 30 seconds to programme once you have Canlib downloaded on the host computer, USBcan Light 2xHS is simple to install and configure. Major features of the USBcan Light 2xHS:

- One USB 2.0 compliant device provides easy access to two CAN busses
- Quick end easy plug-and-play installation
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers
- 100% compatible with applications written for other Kvaser CAN hardware with Kvaser CANlib
- High speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s
- Fully compatible with J1939, CANopen, NMEA 2000R and DeviceNet





Technical Data

Kvaser USBcan Light 2x HS

Galvanic Isolation	Yes
Bitrate	40-1000 kbit/s
Silent mode	NA
Error frame generation	NA
Error frame detection	Yes
Weight	150g
Timestamp resolution	2 μ s
On board buffer	Yes
Maximum message rate, send	8000
Maximum message rate, receive	8000
Sound	No
Clock synchronization	N/A
Dimensions (WxLxH)	50x90x25mm
Temperature range	-20°C to +70°C
Order number	73-30130-00714-7

The information herein is subject to change without notice